In Java, constants and variables are used to store and manipulate data.

They represent named memory locations that hold values of different types.

Here's a brief explanation of constants and variables in Java:

1. Constants:

- Constants are identifiers whose values cannot be changed once they are assigned.
- In Java, constants are typically declared using the final keyword, which makes them unmodifiable.
- Constants are commonly used to represent fixed values, such as mathematical constants, configuration settings, or any value that should remain constant throughout the program.
- Constants can be of primitive types (e.g., int, double, char) or reference types (e.g., String, Object).

Example:

```
final int MAX_VALUE = 100;
final double PI = 3.14159;
final String MESSAGE = "Welcome!";
```

2. Variables:

• Variables are identifiers that hold data that can be modified during the program's execution.

- Variables are declared by specifying the data type followed by the variable name.
- Variables can store values of primitive types or references to objects.
- The value of a variable can be assigned, updated, and used in various operations.

Example:

```
int age = 25;
double salary = 5000.0;
String name = "John Doe";
```

- 3. Variable Naming Rules:
 - Variable names in Java should follow certain rules:
 - They must start with a letter (a-z or A-Z), underscore (_), or dollar sign (\$).
 - After the first character, they can include letters, digits (0-9), underscores, or dollar signs.
 - Variable names are case-sensitive.
 - It's recommended to use meaningful names that reflect the purpose of the variable.
 - Reserved words (keywords) cannot be used as variable names.

4. Variable Initialization:

- Variables should be initialized with a value before they are used.
- Uninitialized variables have a default value depending on their data type (e.g., 0 for numeric types, false for boolean, null for reference types).

Example:

```
int x; // Uninitialized variable
x = 10; // Variable initialization
```

int y = 20; // Declaration and initialization in a single statement

Difference between Contants and Variables in Java :

	Constants	Variables
Definition	Named memory locations with unchangeable values	Named memory locations with changeable values
Declaration	Declared using the final keyword	Declared without the final keyword
Value	Value cannot be modified once assigned	Value can be modified during program execution
Naming	Typically named using uppercase letters and underscores	Typically named using lowercase letters and camel case
Usage	Used to represent fixed values that remain constant throughout the program	Used to store and manipulate data during program execution
Data Type	Can be of primitive types or reference types	Can be of primitive types or reference types
Initialization	Must be initialized at the time of declaration or in a constructor/block	Must be initialized before use or assigned a value during runtime
Example	final int MAX_VALUE = 100;	int count = 0;

Java in Hindi Video

Related Posts:

- 1. Can Java have same name variable
- 2. Types of variables in Java programming
- 3. JAVA and its Support Systems
- 4. JAVA environment
- 5. JAVA program structure
- 6. Tokens
- 7. Java statements
- 8. Java virtual machine
- 9. C++ Versus JAVA
- 10. Data types JAVA
- 11. Defining a class
- 12. Constructor in JAVA
- 13. Array in Java
- 14. Applet
- 15. Applets Vs Applications
- 16. Writing applets
- 17. Applets life cycle
- 18. Creating an Executable Applet
- 19. Graphics in Applet
- 20. Applet image display
- 21. Applet digital clock
- 22. Applet mouse event handling
- 23. JDBC
- 24. Execute an SQL Statement
- 25. Process the result
- 26. CLOSE THE DATABASE CONNECTION

- 27. File handling
- 28. Define a class to declare an integer array of size n and accept the elements into the array.
- 29. Define a class to declare an array of size 20 of the double datatype, accept the elements into the array and perform the following: Calculate and print the sum of all the elements.
- 30. Java program for String, to uppercase, to equal, length of string
- 31. Write a Java program for Buble sort.
- 32. Write a Java program String to uppercase and count words startig with 'A'
- 33. How to set path in Java
- 34. Understanding public static void main (String args[]) { } in Java
- 35. Difference between static and non static methods in Java