

Java has several built-in data types that are used to define the type of data that can be stored in variables.

Here are the primary data types in Java:

## 1. Primitive Data Types:

- byte: Represents a signed 8-bit integer (-128 to 127).
- short: Represents a signed 16-bit integer (-32,768 to 32,767).
- int: Represents a signed 32-bit integer (-2,147,483,648 to 2,147,483,647).
- long: Represents a signed 64-bit integer (-9,223,372,036,854,775,808 to 9,223,372,036,854,775,807).
- float: Represents a single-precision 32-bit floating-point number.
- double: Represents a double-precision 64-bit floating-point number.
- boolean: Represents a boolean value (true or false).
- char: Represents a single Unicode character.

## 2. Reference Data Types:

- String: Represents a sequence of characters.
- Arrays: Represents a collection of elements of the same type.
- Classes: Represents user-defined objects and classes.

It's important to note that primitive data types are basic and have a fixed size in memory, while reference data types are more complex and can be of variable size.

Additionally, Java also supports type conversion between different data types through casting and provides wrapper classes (e.g., Integer, Double, Boolean) that allow primitive data types

to be treated as objects.

Example usage:

```
int age = 25;
double salary = 5000.0;
boolean isActive = true;
char grade = 'A';

String name = "John Doe";
int[] numbers = {1, 2, 3, 4, 5};
```

Related posts:

1. Can Java have same name variable
2. Types of variables in Java programming
3. JAVA and its Support Systems
4. JAVA environment
5. JAVA program structure
6. Tokens
7. Java statements
8. Java virtual machine
9. C++ Versus JAVA
10. Constants and Variables in Java
11. Defining a class
12. Constructor in JAVA
13. Array in Java
14. Applet

15. Applets Vs Applications
16. Writing applets
17. Applets life cycle
18. Creating an Executable Applet
19. Graphics in Applet
20. Applet image display
21. Applet digital clock
22. Applet mouse event handling
23. JDBC
24. Execute an SQL Statement
25. Process the result
26. CLOSE THE DATABASE CONNECTION
27. File handling
28. Define a class to declare an integer array of size n and accept the elements into the array.
29. Define a class to declare an array of size 20 of the double datatype, accept the elements into the array and perform the following: Calculate and print the sum of all the elements.
30. Java program for String, to uppercase, to equal, length of string
31. Write a Java program for Bubble sort.
32. Write a Java program String to uppercase and count words starting with 'A'
33. How to set path in Java
34. Understanding public static void main (String args[] ){ } in Java
35. Difference between static and non static methods in Java