

FC CONNECTIVITY

The FC architecture supports three basic interconnectivity options point to point , arbitrated loop ,and Fibre Channel switched fabric.

POINT-TO-POINT

1. Point-to-point is simplest FC configuration in which two devices are connected directly to each other.
2. This configuration provides a dedicated connection for data transmission between nodes.
3. The point-to-point configuration offers limited connectivity , because only two devices can communicate with each other at a given time.
4. It can not be scaled to accommodate a large number of nodes.
5. Standard DAS uses point-to-point connectivity.

Point-to-Point




Fig. point to point connectivity

FIBRE CHANNEL ARBITRATED LOOP

1. In FC-AL configuration devices are attached to a shared loop.

2. FC-AL has a characteristics of a token ring topology and a physical star topology.
3. In FC-AL each device contents with other devices to perform I/O operations.
4. Devices on the loop must “arbitrated” to gain control of the loop. At any given time , only one device can perform I/O operations on the loop.
5. The FC-AL implementation may also use hubs whereby the arbitrated loop is physically connected in a star topology.

Related posts:

1. Information Life Cycle Management (ILM)
2. Storage infrastructure
3. Integrated VS Modular Array
4. Data proliferation
5. Data categorization
6. Component architecture of intelligent disk subsystem
7. Intelligent disk subsystems overview
8. Mapping n operations
9. Storage system architecture
10. RAID
11. Hot spare
12. SAN security
13. JBOD
14. Elements of DAS,NAS,CAS,SAS
15. Limitations of DAS
16. Cloud vocabulary
17. NAS security
18. Management of DAS,NAS,CAS,SAN

- 19. Memory virtualization
- 20. Data center concepts & requirements
- 21. Network virtualization
- 22. Server information storage and management
- 23. ISM Architectural Framework