

1. What is the purpose of jointing in masonry construction?

- a) To provide structural integrity
- b) To enhance aesthetic appeal
- c) To prevent water infiltration
- d) To increase thermal insulation

*Answer: c) To prevent water infiltration*

Jointing in masonry construction involves filling the gaps between bricks or stones with mortar to create a cohesive structure and to prevent the ingress of water, which could otherwise weaken the wall and lead to structural damage.

2. Which type of bond is commonly used in brick masonry for its strength and stability?

- a) English bond
- b) Flemish bond
- c) Stretcher bond
- d) Header bond

*Answer: b) Flemish bond*

Flemish bond is a type of brick bonding pattern where alternating headers and stretchers are laid in each course. It is favored for its stability and aesthetic appeal.

3. What is the primary purpose of a cavity wall in construction?

- a) To reduce heat transfer

- b) To increase structural strength
- c) To enhance acoustic insulation
- d) To provide architectural detail

*Answer: a) To reduce heat transfer*

Cavity walls consist of two parallel walls (skins) with a gap (cavity) between them. This design helps to reduce heat transfer through the wall, thereby improving thermal insulation and energy efficiency.

4. What is a common defect in masonry construction that can adversely affect the strength and performance of walls?

- a) Efflorescence
- b) Spalling
- c) Laitance
- d) Honeycombing

*Answer: d) Honeycombing*

Honeycombing refers to voids or incomplete filling of mortar within the masonry wall, leading to reduced structural integrity and increased vulnerability to moisture infiltration and cracking.

5. What is the function of a window sill in construction?

- a) To support the window frame
- b) To provide drainage for rainwater

- c) To enhance architectural detail
- d) To prevent water ingress

*Answer: b) To provide drainage for rainwater*

Window sills are sloped elements located beneath the bottom rail of a window frame. Their primary function is to shed rainwater away from the wall and prevent moisture infiltration into the building envelope.

6. Which type of window frame material is known for its durability and resistance to corrosion?

- a) Wood
- b) Aluminum
- c) PVC (Polyvinyl chloride)
- d) Steel

*Answer: d) Steel*

Steel window frames are renowned for their strength, durability, and resistance to corrosion, making them suitable for various applications, including in harsh environmental conditions.

7. What is the purpose of a sunshade in architectural design?

- a) To provide shade and reduce solar heat gain
- b) To enhance visual appeal
- c) To support climbing plants
- d) To protect windows from damage

*Answer: a) To provide shade and reduce solar heat gain*

Sunshades are architectural elements designed to provide shade and mitigate solar heat gain, thereby improving indoor comfort and reducing the energy consumption of buildings.

8. What is the primary advantage of using precast stone masonry in construction?

- a) Cost-effectiveness
- b) Speed of installation
- c) Customizability
- d) Enhanced structural integrity

*Answer: b) Speed of installation*

Precast stone masonry involves casting stone elements off-site and then transporting them to the construction site for assembly. This method offers the advantage of faster installation compared to traditional stone masonry, contributing to shorter construction schedules.

9. What is the purpose of plastering in masonry construction?

- a) To improve aesthetic appearance
- b) To provide waterproofing
- c) To enhance structural strength
- d) To increase thermal insulation

*Answer: a) To improve aesthetic appearance*

Plastering involves applying a smooth and even layer of mortar or gypsum plaster to masonry

surfaces to create a uniform and aesthetically pleasing finish.

10. What is the primary function of distempering in wall finishing?

- a) To provide waterproofing
- b) To increase durability
- c) To enhance aesthetic appeal
- d) To improve thermal insulation

*Answer: c) To enhance aesthetic appeal*

Distempering is a method of wall finishing that involves applying a mixture of water, chalk, and pigment to create a decorative and colorful surface. It is primarily used to enhance the aesthetic appeal of walls.

11. What is a common rule of proportionality in stair design?

- a) Rise-to-run ratio
- b) Tread width
- c) Baluster spacing
- d) Handrail height

*Answer: a) Rise-to-run ratio*

The rise-to-run ratio, also known as the pitch or slope of a stair, is a common rule of proportionality in stair design. It refers to the relationship between the height of each step (rise) and its depth (run), ensuring comfortable and safe stair ascent and descent.

12. What is the purpose of a damp-proof course in masonry construction?

- a) To prevent rising damp
- b) To enhance structural stability
- c) To improve thermal insulation
- d) To increase fire resistance

*Answer: a) To prevent rising damp*

A damp-proof course (DPC) is a barrier typically installed horizontally in the walls near ground level to prevent moisture from rising through capillary action and causing dampness in the building structure.

13. Which type of window is designed to pivot horizontally for ventilation?

- a) Casement window
- b) Awning window
- c) Horizontal sliding window
- d) Pivot window

*Answer: d) Pivot window*

Pivot windows are designed to rotate horizontally around a central pivot point, allowing for controlled ventilation and ease of cleaning from the inside of the building.

14. What is the primary purpose of pointing in masonry construction?

- a) To enhance structural stability

- b) To improve thermal insulation
- c) To provide waterproofing
- d) To increase aesthetic appeal

*Answer: c) To provide waterproofing*

Pointing involves filling the joints between bricks or stones with mortar to seal them against water infiltration, thereby enhancing the waterproofing of the masonry wall.

15. Which type of door frame material is known for its resistance to termite damage?

- a) Wood
- b) Aluminum
- c) Steel
- d) PVC (Polyvinyl chloride)

*Answer: d) PVC (Polyvinyl chloride)*

PVC door frames are resistant to termite damage, making them a suitable choice for areas prone to termite infestation. Additionally, PVC frames require minimal maintenance and offer good thermal insulation properties.