

1. A transmitter transmits the frame.
2. Transmitter wait for the acknowledgement for fixed period of time.
3. On receiving valid frame, receiver send back an acknowledgement for next frame.
4. On receiving acknowledgement transmitter transmit next frame.
5. If sender not received any acknowledgement within time duration it re-transmit the same frame.
6. The rate of transmission depends on the processing power of the receiver.

**Example of Stop and Wait protocol.**

Frame Sender	Frame Receiver
Frame(0) transmitted	Acknowledgement Frame(1)
Frame(1) transmitted	Acknowledgement Frame(2)
Frame(2) transmitted	No Acknowledgement within time
Frame(2) re-transmitted	Acknowledgement Frame(3)

This method is ineffective when the size of the frame is large.

**What if the size of the frame is large?**

1. The transmitter divides large messages into smaller frames.
2. Then transmit these smaller frames.



---

## Related Posts:

1. What is computer network
2. Data Link Layer
3. Framing
4. Byte count framing method
5. Flag bytes with byte stuffing framing method
6. Flag bits with bit stuffing framing method
7. Physical layer coding violations framing method
8. Error Control in Data link layer
9. Sliding Window Protocol
10. One bit sliding window protocol
11. A Protocol Using Go-Back-N
12. Selective repeat protocol
13. Net 10
14. Net 9
15. Net 47
16. Net 43
17. OSI vs TCP/IP
18. TCP/IP Reference Model
19. OSI Reference Model
20. Computer Networks Introduction
21. Types of Computer Networks
22. Network Architectures



- 23. Computer Network Topologies
- 24. LAN and WAN Protocols
- 25. Network Address
- 26. IP Addresses
- 27. Class Full Addressing
- 28. Networking Media
- 29. Networking Devices
- 30. Structured cabling
- 31. Types of connectivities in Computer Networks
- 32. Introduction to Network Operating System(NOS)
- 33. ARP/RARP
- 34. Cooperative Caching